



End View  
(not to scale)

**MULTI FLOUT® Arrangement with four 3" outlets. Type FL-xx34 Flout® (xx= drawdown in inches)**

**Notes:**

\*Dimensions are required minimums. All dimensions originate from inside of chamber. All dimensions in inches.

\* **MINIMUM DRAWDOWN** available for this arrangement: 6"

\* **MAXIMUM DRAWDOWN** available for this arrangement: 55"

\* **SHIM:** Flout devices shall not drop lower than the outlet. Excessive drop will result in slow or no shut-off of flow. Install a shim to support Flout if floor is lower than outlets. Shims may be made of masonry or other suitable material. Plastic shim arrangements are available. Shims shall support Flout completely and be non-perforated to provide a water cushion. Consult Rissy for shim options.

\* **FLOW DIVERTER:** Inlet flow shall not enter or interfere with the Flout. Divert inlet flow with a tee, elbow, or similar baffle to a level equal to or slightly below low liquid level.

\* Flow rates and capacities depend on size of tank and drawdown used. This diagram is for a TYPICAL system.

**Rissy Plastics, LLC**  
350 Cedar Lane  
860.482.1645  
860.482.1645  
fax 860.482.8800  
www.flout.net larvris@aol.com



**MULTIPLE OUTLET FLOUT®  
DOSING CHAMBER (TYPICAL)**

Date: 4/2/10

Dwg No: fltyp\_flxx34

Scale: 3/4" = 12"

Inches

Flout® US Patent 5290434

CueBox™ US Patent Pending